


ASDF-1013-06 Ligature-resistant Wall Mounted 18" Wide Drinking Fountain



(Unit may be shown with optional features)

To specify fixture and accessories, use the Model Number and Options page.

Example: To specify a Ligature-resistant, Wall Mounted, 18" Wide Drinking Fountain with standard ligature-resistant drinking fountain bubbler, single temp electronic valve, piezo push button, standard elbow waste (with thru-wall extension, 'p'-trap, and clean-out), and wall sleeve

Use the following Willoughby Model Number:

ASDF-1013-06-DMBH-E1L1-PZPB-EB-LW1-WS

Recommended Specifications

Ligature-resistant, Wall Mounted, 18" Wide Drinking Fountain shall be: Willoughby Model No. **ASDF-1013-06**
(select from model number and options list on next page)

Fixture shall be fabricated from 14 gauge, type 304 stainless steel. The construction shall be all-welded, with exposed stainless surfaces polished to a #4 satin finish.

Standard equipment shall include:

- Oval-shaped basin, 13" x 9-1/2" x 1-1/2" deep
- Integral slow drain with air vent
- (DMBH) deck-mounted ligature-resistant stainless steel drinking fountain bubbler
- (PSL1) Single temperature, non-metering pneumatic valve w/ (PBH) ligature-resistant pneumatic push button
- (EB) elbow waste (1-1/2" F.I.P.)

Cabinet interior shall be sound deadened with fire-resistant material.

Mounting:

Anchoring shall be by standard 4-point system: Ø1/2" threaded rods, nuts, and washers shall be furnished for walls up to 8" thick. Unit shall require chase area for installation and maintenance.

Unit shall require chase area for installation and maintenance.

Vandal Resistance:

All push buttons and escutcheons are secured to the unit from within the fixture. Valves, water supplies and waste connections are concealed within.

visit our website at www.willoughby-ind.com

5105 West 78th Street • Indianapolis, IN. 46268

(317) 875-0830 • Fax: (317) 875-0837 • (800) 428-4065



MADE IN THE U.S.A.

MODEL NUMBER AND OPTIONS:

1.) Drinking Fountain Model:

- ASDF-1013-06 Ligature-resistant, Wall Mounted, 18" Wide Drinking Fountain

2.) Bubbler Selection:

- DMBH Deck Mounted Ligature-resistant Bubbler (Standard)

3.) Valve Selection:

- PSL1 Single Temp. Pneumatic Non-metering (Standard)
- PML1 Single Temp. Pneumatic Metering
- E1L1 Single Temp. Electronic*

4.) Push Button Selection:

- PBH Ligature-resistant Pneumatic Push Button (Standard)
- EPBH Ligature-resistant Electronic Push Button*
- PZPB Piezo Push Button*

5.) Drinking Fountain Waste:

- EB Elbow Waste (Standard)
- PT Integral 'P'-Trap
- LWE Lavatory Waste Extension
- LW1 Thru-Wall Extension, 'P'-Trap, and Clean-Out
- LW2 Thru-Wall Extension and Clean-Out


6.) Other Options:

- MT Wall Template
- WS Wall Sleeve (Requires Accessible Chase)
- Other: _____
- Other: _____

*(Req. 110V power through ground fault interrupter (GFCI) receptacle)

Approved For Manufacturing By: _____ Date: _____ Company: _____
 Wall Thickness: _____ Wall Type: _____

VERIFY ALL DIMENSIONS WITH FACTORY PRIOR TO ROUGH-IN
 WILLOUGHBY RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN AND DIMENSIONS WITHOUT FORMAL NOTICE AND WITHOUT INCURRING OBLIGATION.



visit our website at www.willoughby-ind.com
 5105 West 78th Street • Indianapolis, IN. 46268
 (317) 875-0830 • Fax: (317) 875-0837 • (800) 428-4065



MADE IN THE U.S.A.